

KemaPox HF 022

Description: Aliphatic amine curing agent – Triethylenetetramine

Fields of applications:

- **KemaPox HF 022** is mainly used in combination with suitable epoxy resin formulations for highly reactive systems and as accelerator for polyamide curing agents.
- Is used in maintenance paints, in adhesives and in combination with other hardeners for various applications.

Specification:

Appearance	clear liquid	
Content	> 96 %	
Water content	<= 0.1 %	DIN/ISO 51777
Color pt.-Co	max 50	

Characteristic data:

H*-equivalent mass	24	
Viscosity at 23 °C	30 mPas	DIN 525672
Density at 23 °C	0.974 g/cm ³	DIN 53217
Vapour pre. at 23 °C	5 Pa	
Solidification point	- 35 °C	

Storage life: It is at least 24 months, at room temperature in the original sealed containers, from the date of manufacture.

Handling Precautions: Please refer to the Safety data sheet of this product.

Classification: C "corrosive".

The information provided herein is considered to be representative of our production, and is to the best of our knowledge accurate and according to our laboratory tests and data which we believe to be reliable. This does not construe in any way any liability or responsibility from our part for any third party since the conditions of use are beyond our control and each user should perform sufficient investigation to establish the full suitability of our products for its intended use. Furthermore no information provided here should be taken as a recommendation or advice for infringement of third party intellectual property rights.