

KemaPox HF 020

Description: Cycloaliphatic Diamine –Isophorone Diamine

Fields of applications :

- **KemaPox HF 020** is a high-performance hardener for liquid, solvent-free epoxy resins.
- Is used together with other hardener components to formulate with corresponding epoxy-system as a wide range of products, e.g. for floor-coatings, adhesives , solvent-free primers and paints etc.

Specification:

Appearance	clear liquid	
Content	> 99 %	
Water content	<= 0.2 %	DIN/ISO 51777
Color (APHA)	max 15	DIN/ISO 6271

Characteristic data:

H*-equivalent mass	42.6	
Viscosity at 23 °C	14 mPas	DIN 525672
Density at 23 °C	0.92 g/cm ³	DIN 53217
Flash point	117 °C	DIN-52758
Solidification point	+ 10 °C	

Storage life: It is at least 24 months, at room temperature in the original sealed containers, from the date of manufacture.

Handling Precautions: Please refer to the Safety data sheet of this product.

Classification: C "corrosive".

The information provided herein is considered to be representative of our production, and is to the best of our knowledge accurate and according to our laboratory tests and data which we believe to be reliable. This does not construe in any way any liability or responsibility from our part for any third party since the conditions of use are beyond our control and each user should perform sufficient investigation to establish the full suitability of our products for its intended use. Furthermore no information provided here should be taken as a recommendation or advice for infringement of third party intellectual property rights.