

KemaPox EM 260

Description: A branched-urethane-polymer with blocked, isocyanate groups which can be cured using amine hardeners.

Fields of applications:

- **KemaPox EM 260** is used essentially for the internal modification of epoxy systems to impart to them flexibility and toughness.
- The different applications include coatings, sealing membranes and joint filler.

Specification:

Viscosity at 23 °C	77000 - 120000 mPas	DIN 53214
Density at 23 °C	app. 1.05 g/cm ³	DIN 51757,T3
Flash Point	> 190 °C	DIN-ISO 2719

Characteristic data:

Epoxy Equivalent Wt.	900-930 g/eq.	
Reactive NCO	app.2.5 %	
Free isocyanate content	< 0.2 %	

Storage life: It is at least 24 months, at room temperature in the original sealed containers, from the date of manufacture.

Handling Precautions: Please refer to the Safety data sheet of this product.

The information provided herein is considered to be representative of our production, and is to the best of our knowledge accurate and according to our laboratory tests and data which we believe to be reliable. This does not construe in any way any liability or responsibility from our part for any third party since the conditions of use are beyond our control and each user should perform sufficient investigation to establish the full suitability of our products for its intended use. Furthermore no information provided here should be taken as a recommendation or advice for infringement of third party intellectual property rights.