

KemaPox EXPL-5

Description Hydroxy Modified Resin

Fields of applications:

- KemaPox EXPL-5 is an epoxy modifier with low viscosity enabling production of spray applied epoxy systems.
- It has low vapor pressure and low toxicity.

It gives excellent substrate and filler wetting characteristics with improved flexibility and reduced reactivity.

Specification:

Viscosity at 25 °C	app 350 mPas	DIN 53214
Density at 25 °C	1.01 g/cm ³	DIN 51757,T3
Color index	< 2	Gardner

Characteristic data:

Hydroxyl Number	56	
Percent Volatile,	1.5	1 gram/2hrs/100 °C
Flash point Closed cup °C	310	DIN 51777

Storage life: It is at least 24 months, at room temperature in the original sealed containers, from the date of manufacture.

Handling Precautions: Please refer to the Safety data sheet of this product.

The information provided herein is considered to be representative of our production, and is to the best of our knowledge accurate and according to our laboratory tests and data which we believe to be reliable. This does not construe in any way any liability or responsibility from our part for any third party since the conditions of use are beyond our control and each user should perform sufficient investigation to establish the full suitability of our products for its intended use. Furthermore no information provided here should be taken as a recommendation or advice for infringement of third party intellectual property rights.