

KemaPur PCU 200S

Description: A polycarbonate, 2K waterborne matte coating and sealer with excellent abrasion and scratch resistance as well as chemical resistance.

Fields of applications:

- **KemaPur PCU 200S** is used for the sealing concrete and screed surfaces as well as on polymeric surfaces such as epoxy and polyurethane floors, both indoors and outdoors.
- It is chemically resistant to a variety of alkalis, acids and solvents plus the product is environmentally friendly being water borne.

Specification:

| | | |
|---------------------------|-------------------|--------------|
| Percent solids | app. 40 % | |
| Mix Ratio A : B | 100 : 10 gm. | by weight |
| Pot life at 23 °C | app. 7 hrs. | |
| Hardness | app. 90 | DIN ISO 1522 |
| Tensile strength | app 24 MPa. | DIN-ISO 527 |
| Elongation at tear | app 8 % | DIN-ISO 527 |
| Rate of usage | 120 – 150 gm./ m2 | |

Storage life: It is at least 6 months, above freezing in the original sealed containers, from the date of manufacture.

Handling Precautions: Please refer to the Safety data sheet of this product.

The information provided herein is considered to be representative of our production, and is to the best of our knowledge accurate and according to our laboratory tests and data which we believe to be reliable. This does not construe in any way any liability or responsibility from our part for any third party since the conditions of use are beyond our control and each user should perform sufficient investigation to establish the full suitability of our products for its intended use. Furthermore no information provided here should be taken as a recommendation or advice for infringement of third party intellectual property rights.